Vikram Madan et al. – U.S. Application No. 10/766,319

Amendments to the Specification:

Please amend paragraph 33 (starting on page 7, line 19) as follows:

[01]A number of program modules can be stored on the hard disk drive 170, magnetic disk 190, optical disk 192, ROM 140 or RAM 150, including an operating system 195, one or more application programs 196, other program modules 197, and program data 198. A user can enter commands and information into the computer 100 through input devices such as a keyboard 101 and pointing device 102. Other input devices (not shown) may include a microphone, joystick, game pad, satellite dish, scanner or the like. These and other input devices are often connected to the processing unit 110 through a serial port interface 106 that is coupled to the system bus, but may be connected by other interfaces, such as a parallel port, game port or a universal serial bus (USB). fat this point in time, since USB is so popular, you might want to feature USB in Figure 1] Further still, these devices may be coupled directly to the system bus 130 via an appropriate interface (not shown). A monitor 107 or other type of display device is also connected to the system bus 130 via an interface, such as a video adapter 108. In addition to the monitor, personal computers typically include other peripheral output devices (not shown), such as speakers and printers. In one embodiment, a pen digitizer 165 and accompanying pen or stylus 166 are provided in order to digitally capture freehand input. Although a direct connection between the pen digitizer 165 and the serial port interface 106 is shown, in practice, the pen digitizer 165 may be coupled to the processing unit 110 directly, parallel port or other interface and the system bus 130 by any technique including wirelessly. Also, the pen 166 may have a camera associated with it and a transceiver for wirelessly transmitting image information captured by the camera to an interface interacting with bus 130. Further, the pen may have other sensing systems in addition to or in place of the camera for determining strokes of electronic ink including accelerometers, magnetometers, and gyroscopes.